

# 20' RDS Flat Pack

<b>Basic Features</b>
<b>External size:</b> 6058X2438X2591mm/20'x8'x8'6'' <b>Internal Size:</b> 5886X2266X2330mm
<b>Tare weight:</b> 1700 kg
<b>Roof:</b> <ul style="list-style-type: none"><li>➤ <b>Insulation Thickness:</b> 100 mm</li><li>➤ <b>Exterior Covering:</b> 0.5 mm PPG, double folded along whole container length</li><li>➤ <b>Interior Covering:</b> 0.5 mm PPG</li><li>➤ <b>Top end / side rail:</b> t3.0mm Q235A</li></ul>
<b>Floor:</b> <ul style="list-style-type: none"><li>➤ <b>Insulation Thickness :</b> 110 mm</li><li>➤ <b>Sub-floor:</b> t0.5mm PPZ</li><li>➤ <b>Bottom end / side rail:</b> t4.0mm Q235A</li><li>➤ <b>Cross-member:</b> t3.0mm Q235A</li><li>➤ <b>Floor Plate:</b> t20mm Plywood</li><li>➤ <b>PVC Plate:</b> t2.0mm PVC as marble color</li><li>➤ <b>Forklift pocket opening in 250x84, the centre distance is 1500mm</b></li></ul>
<b>Side walls:</b> <ul style="list-style-type: none"><li>➤ <b>Insulation Thickness:</b> 50 mm</li><li>➤ <b>PPG+Insulation+PPG with small corrugation</b></li><li>➤ <b>With two windows which are made of steel reinforced plastic,the dimension is 890x890mm</b></li></ul>
<b>Front Frame:</b> <ul style="list-style-type: none"><li>➤ <b>Insulation Thickness:</b> 50 mm</li><li>➤ <b>PPG+ Insulation +PPG with small corrugation</b></li></ul>
<b>Rear Frame:</b> <ul style="list-style-type: none"><li>➤ <b>Insulation Thickness:</b> 50mm</li><li>➤ <b>PPG+ Insulation +PPG</b></li><li>➤ <b>Rear frame is the inserted type with two panels, one of them with door and switch.</b></li><li>➤ <b>The door's dimension is 900x2100 with 35mm altitudinal door sill and has three hinge at right</b></li><li>➤ <b>The material of the door is aluminium alloy</b></li></ul>
<b>Corner Posts:</b> <ul style="list-style-type: none"><li>➤ <b>Total four sets corner posts</b></li><li>➤ <b>T3.0mm Q235A</b></li><li>➤ <b>Fitted with the base and roof frame with screws</b></li></ul>
<b>Preservation:</b> <ul style="list-style-type: none"><li>➤ <b>The outside panel's colour of all side wall usually be chosen among RAL5020、RAL7035 and RAL1014</b></li><li>➤ <b>Container frame can be painted same as outside panel of side wall</b></li></ul>
<b>Insulation material Option:</b> <ul style="list-style-type: none"><li><input type="checkbox"/> <b>Rock Wool (basic version)</b></li><li><input type="checkbox"/> <b>Polystyrene (PS)</b></li><li><input type="checkbox"/> <b>Polyurethane (PU)Foam</b></li></ul>

Intercon Modular, LLC  
www.inter-con.us  
+1-801-705-4567  
(f) +1-801-2212587  
richard.hill@inter-con.us



**Intercon Modular, LLC**  
**www.inter-con.us**  
**+1-801-705-4567**  
**(f) +1-801-2212587**  
**richard.hill@inter-con.us**

